



SOFTCOURT

3 mm

**OUTDOOR CUSHIONED
SPORTS FLOORING**

Product	Decoflex™ Softcourt 3 mm	
Description	Decoflex™ Softcourt 3 mm is a dual layer in- and outdoor cushioned sports flooring system comprising of a prefabricated rubber roll base mat, finished with multiple squeegee applied liquid rubber coatings.	
Thickness	3 mm	
Adhesive for base mat	PU88 2-component polyurethane Adhesive	
Base Mat	Prefabricated rubber base mats supplied in rolls, 1.5 m wide, to the specified thickness. Density 850 kg/m ³ .	
Decoflex™ Softcourt 3 mm	Test	Result
Force Reduction	DIN 18035	10%
Vertical Deformation	DIN 18035	0.31 mm
Taber Abrasion [Wheel H18, 1000 gr]	ISO 5470-1	0.31 gr
Friction	DIN 18035	<i>Dry</i> 0.62 <i>Wet</i> 0.56
Indentation	DIN 18035	<i>When loaded</i> 0.50 mm <i>Remaining</i> 0.07 mm
Tensile Strength	DIN 18035	0.99 N/mm ²
Elongation at Break	DIN 18035	50%
Ball Rebound	DIN 18035	99%
Flammability	DIN 51960	Class 1
ITF Pace Classification	ITF	Category 2 - medium fast