

## Safety flooring has never looked this good.

Neoflex<sup>™</sup> Resilient Flooring stands out as an innovative, aesthetic and environmentally-friendly choice for pool surrounds. It is a single-ply rubber safety floor that is flexible and will not crack, peel or delaminate.

In today's world, where safety flooring is a functional necessity for recreational installations, Neoflex<sup>™</sup> is a perfect choice for the most demanding of resilient pool surrounds, changing rooms, patios, terraces and other high traffic areas. Made of the highest quality synthetic rubber, Neoflex<sup>™</sup> has an international reputation for durability, resilience, anti-slip safety, comfort and good design.

Neoflex<sup>™</sup> is treated with a microbial preservative to ensure added value in the form of lasting micro-organism resistance and a longer useful life. You can count on Neoflex<sup>™</sup> safety flooring for many years of trouble free use.




SPECIFICATIONS

Thickness	3 - 12 mm (1/8" - 1/2")	
Roll Length	10 -25 m (50')	
Roll Width	1.2 m (4')	
Density	± 1,300 kg/m <sup>3</sup> (81.04 lbs/cu. ft.)	
Resilience	40%	DIN 18032
Tensile Strength	0.91 N/mm <sup>2</sup>	DIN 18032
Tear Strength	9.7 N/mm	ASTM D624
Taber Abrasion	0.66 gr	ASTM C504
Shore Hardness A	60	ASM D2240
Remaining Indentation	0.05 mm	DIN 53960
Noise Absorption	13dB [4 mm]	EN 20140/ISO 140
Flammability	Class 1 (Sport Use)	ASTM D2859
Flammability	Cfl-s1 (Commercial Use)	EN 13501
Flammability	Class 1 (Commercial Use)	ASTM E648
Coefficient of Friction	Dry 1.1, Wet 1.03	ASTM D2047-97
Slip Resistance	R10	ANZS 4596:1999
Thermal Stability	-40°C to 100°C	ASTM C1026

## www.rephouse.com


## **Original Colors**




603




633







609



635



628




636







600-101




600-105



600-109



600-113




600-117




600-102



600-106



600-110




600-114




600-118



600-103



600-107




600-111




600-115



600-119







600-104




600-108



600-112



600-116



600-120



REP-2010 GEGA2S-2005-FLOOR COVERINGS