



## Performance can take many forms. The most beautiful is presented here.


Neoflex™ is prefabricated rubber flooring made of polymerically bound recycled and synthetic rubbers. It is a designer's dream - Neoflex™ 600 Series is a high-density sheet floor that is evocative of terrazzo style flooring, while also being sound insulating, flexible and durable. Neoflex™ 600 Series is made entirely of Mixed Colored EPDM Rubber, and is thus suitable for all interior fitness and gym applications, as well as entrances, changing rooms, and corridors.

Characteristic	Test Method	600 Series
Thickness		3 mm to 10 mm
Roll Width		1.20 m
Density		1,300 kg/m <sup>3</sup>
Resilience	DIN 18032-2	40%
Tensile Strength	DIN 18032-2	0.91 N/mm <sup>2</sup>
Tear Strength	ASTM D 624	9.7 N/mm
Taber Abrasion	ASTM C 504	0.66 gm
Shore Hardness	ASTM D 2240	60
Remaining Indentation	DIN 53960	0.05 mm
Noise Absorption	EN 21040 / ISO 140	13 dB (4 mm)
Stainability	ASTM D 543-95	
	Alcohol	No Change
	Ammonia	No Change
Coefficient of Friction	ASTM D 2047-97	Dry: 1.10 Wet: 1.03
Slip Resistance	AS/NZS 4586:2004	48 Mean BPM, Class W
Thermal Stability	ASTM C 1026	-40°C to 100°C
Flammability	EN 13501	Efl or Cfl-s1
Total VOC	ASTM D 5116	< 0.3 mg/m <sup>2</sup> /hr





# Standard Colors




603




609




633



634




635



636



665




675




600-001




600-002




600-003




600-004




600-005




600-006




600-007




600-008




600-009




600-010




600-011



600-012




600-013




600-014



600-015




600-016




600-017



600-018



600-019



600-020

# A Small Sampling of our Standard Colors

We have many more... or you can even create your own custom color. Contact us!